



**PHASICS**  
The phase control company

# SID4 SWIR

## COST-EFFECTIVE SHORT WAVE IR WAVEFRONT SENSOR

The SID4 SWIR wavefront sensor integrates PHASICS patented technology with an InGaAs detector. Thanks to its high spatial resolution (80 x 64 phase pixels) and high sensitivity, it offers accurate wavefront measurement from 900 nm to 1.7 $\mu$ m. SID4 SWIR is an innovative solution for testing SWIR lens used in optical communications, inspection instruments or night vision in military and surveillance devices.

**APPLICATIONS:** [Laser industry](#) | [FSOC](#) | [Automotive](#) | [Aerospace](#) | [Optical components](#)

### SPECIFICATIONS

Wavelength range	0.9 - 1.7 $\mu$ m
Aperture dimensions	9.60 x 7.68 mm <sup>2</sup>
Phase spatial resolution	120 $\mu$ m
Phase & Intensity sampling	80 x 64
Resolution (Phase)	< 2 nm RMS
Accuracy (Absolute)	15 nm RMS
Frame rate	30 fps
Real-time processing frequency	>7 fps (full resolution)*
Interface	Giga Ethernet
Dimensions	100 x 55 x 63 mm <sup>3</sup>
Weight	~ 500g

\* with SID4 software